

Lithium Ion Battery 3 Ton 3.5 Ton 4 Wheel Electric Forklift Trucks Lift 3M

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Goodsense
- Model Number: FB30
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Bare packaging
- Delivery Time: 30-40work days
- Payment Terms: T/T



Product Specification

- Model Number: FD330
- Rated Loading Capacity: 3 Ton
- Core Components: Motor, Pump, Gearbox
- Weight (KG): 4520 Kg
- Fork Length: 1070mm
- Fork Width: 125mm
- Overall Dimensions: 2741*1230*2115mm
- Rated Capacity: 3000KG
- Place Of Origin: China
- Brand Name: Goodsense
- Name: Forklift
- Condition: New
- Energy Supply: Reference Introduction
- Advantage: Small Vibration And Noise
- Highlight: 3.5 ton 4 wheel electric forklift,



for more products please visit us on rdforklift.com

Product Description



特性	Characteristic		
品型号	Model		FB30
力方式	Power Type		li-ion battery
定 荷量	Rated Capacity	kg	3000
荷中心距	Load Centre	mm	500
自重	Service weight	kg	4520
胎,底	lyre &Chassis		
胎 型(前/后)	Tyre Type(Front/Rear)		充气胎
数量X= (前/后) 数量X= (前/后)	Wheel numberX=drive wheel (Front/Rear)		2X/2
前 胎 格	Tyre Size(Front)		28X9-15-14PR
后 胎 格	Tyre Size(Rear)		6.50-10-10PR

前 距	Front Tread	mm	1000
后 距	Rear Tread	mm	970
距	Wheelbase	mm	1700
尺寸	Size		
叉尺寸(× ×厚)	Fork Size(L×W×T)	mm	1070x125x45
架 角(前/后)	Mast Tilt Angle (F/R)	deg	6/12
架起升高度	Lift Height	mm	3000
架不起升高度	Mast Lowered Height	mm	2115
架最大起升高度(架)	Mast Extended Height	mm	4180
全 (不 叉)	Length to Face of Fork	mm	2741
全 (架)	Overall Width	mm	1230
座椅面至 架距	Distance From Roof to Seat	mm	1020
前 距	Front Overhang	mm	481
后 距	Rear Overhang	mm	575
最小 弯半径	Turning Radius (outside)	mm	2460
最小 地 隙(架)	Ground Clearance	mm	140
性能参数	Performance		
最大行 速度(/空)	Max.Travel Speed (Full load/No load)	km/h	20/20
最大起升速度(/空)	Lifting Speed (Full load/No load)	mm/s	520/530
最大下降速度(/空)	Lowering Speed (Full load/No load)	mm/s	≤600/≥300
最大爬坡度()	Max.Gradeability (Full load)	%	20
,	Power & Transmissions		
池(型)	Battery(Type)		LiFePO4
池(/容量)	Battery(Voltage/Capacity)	V/Ah	309.12/96
引 机功率,S2-60min	Traction Motor Power,S2-60min	Kw	30
起升 机功率,S3-15%	Lifting Motor Power,S3-15%	Kw	30
控制方式	Controller		AC
液 系 工作 力	Operating Pressure	Mpa	18
液 油箱容	Hydraulic Oil Tank Capacity	L	49



Taizhou Ruidong Import and Export Co., Ltd



18367688514



gj_0208@163.com



rdforklift.com

Room 606, East Building 3, Tengda Center, Jiaojiang District, Taizhou, Zhejiang, China